



# Enpeng Bearing Industrial Inc.



## SKF 6220 Ball Bearings 6216, 6218, 6222, 6224, 6226 2RS Zz C3

Bearing No. 6220

6220 Bearing 2D drawings and 3D CAD models

Size	180x100x34 mm
Bore Diameter	180 mm
Outer Diameter	100 mm
Width	34 mm
d	100 mm
D	180 mm
B	34 mm
d <sub>1</sub>	124.8 mm
D <sub>2</sub>	159.9 mm
r <sub>1,2</sub> - min.	2.1 mm
d <sub>a</sub> - min.	112 mm
D <sub>a</sub> - max.	168 mm
r <sub>a</sub> - max.	2 mm
Basic dynamic load rating - C	127 kN
Basic static load rating - C <sub>0</sub>	93 kN
Fatigue load limit - P <sub>u</sub>	3.4 kN
Reference speed	7500 r/min
Limiting speed	4800 r/min
Calculation factor - k <sub>r</sub>	0.025
Calculation factor - f <sub>0</sub>	14.4
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



## Enpeng Bearing Industrial Inc.

Weight / Kilogram	3.23
EAN	7316576622168
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	100MM Bore; 180MM Outside Diameter; 34MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6220
Weight / LBS	7.12
Outside Diameter	7.087 Inch   180 Millimeter
Outer Race Width	1.339 Inch   34 Millimeter
Bore	3.937 Inch   100 Millimeter
bore diameter:	100 mm
static load capacity:	93 kN
outside diameter:	180 mm



## Enpeng Bearing Industrial Inc.

precision rating:	Not Rated
overall width:	34 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	34 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	4800 RPM
internal clearance:	C0
series:	62
dynamic load capacity:	127 kN
$d_1$	124.8 mm
$D_2$	159.9 mm
$r_{1,2}$ min.	2.1 mm
$d_a$ min.	112 mm
$D_a$ max.	168 mm
$r_a$ max.	2 mm
Basic dynamic load rating C	127 kN
Basic static load rating $C_0$	93 kN
Fatigue load limit $P_u$	3.35 kN
Calculation factor $k_r$	0.025
Calculation factor $f_0$	14.4
Mass bearing	3.18 kg